

# ViziPrint®

## Impress Clear UVL

Our optically clear printable window film is designed for trouble-free installation of graphics on glass surfaces. ViziPrint® Impress Clear utilizes a low tack hybrid adhesive technology that creates a strong bond in both high and low temperatures without leaving residue behind. This adhesion technology also eliminates bubbling and is unaffected by moisture. Since it uses a mechanical bond to gently adhere images to windows, the glass stays clear and graphics stay bright whenever ViziPrint® Impress Clear is re-positioned and re-applied. The film is ideal for high quality decals, signage and retail window advertising.

- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- EASY TOOL & BUBBLE FREE APPLICATION
- CAN BE REMOVED WITHOUT LEAVING ADHESIVE RESIDUE

**3**  
mil

Optically  
Clear  
PET

Gloss



**Latex  
UV**



**Hybrid  
Adhesive  
Technology**



**Widths up to 60 in**

YEARS DURABILITY  
**3**

INTERIOR

YEARS DURABILITY  
**2**

EXTERIOR\*

## BEAUTIFUL OPTICALLY CLEAR GRAPHICS



### APPLICATIONS

Smooth Flat Surfaces

Retail Displays

Window Graphics

Decals & Stickers



# DRYTAC®

ADHESIVE SCIENCE

[www.drytac.com](http://www.drytac.com)

## Impress Clear UVL

ViziPrint® Impress Clear is an optically clear PET film with hybrid adhesive technology that is protected by a clear, 1 side siliconized release liner. Its proprietary adhesion technology creates a strong bond in both high and low temperatures without leaving residue behind, eliminates bubbling and is unaffected by moisture. ViziPrint® Impress Clear can be re-positioned and re-applied multiple times, and removes cleanly up to 3 years after installation.

- IDEAL FOR APPLICATIONS ON GLASS AND OTHER SMOOTH, FLAT SURFACES
- IDEAL FOR INTERIOR & SHORT TERM OUTDOOR PROMOTIONS
- CAN BE USED ON ELECTRONIC EQUIPMENT, SUCH AS TV SCREENS, IPAD/TABLET DISPLAYS AND COMPUTER MONITORS, AS WELL AS REFRIGERATORS, GLASS DISPLAY CASES.
- REVERSE PRINTABLE FOR INSIDE MOUNTING OF WINDOW ADVERTISEMENTS.

### INSTALLATION RECOMMENDATION

**Wet or dry installation will work for ViziPrint® Impress Clear. Please see ViziPrint® Impress Clear installation instructions for further details. The surface must be clean and smooth and free of defects before application.**

**For more information, performance and warranty guidelines please contact your local Drytac office.**

© 2022 Drytac Corporation. E&OE.  
All other trademarks are the property of their respective owners.

## TECHNICAL SPECIFICATION

### PRODUCT STRUCTURE

<b>Film</b>	Optically Clear PET
<b>Adhesive</b>	Hybrid Adhesive Technology
<b>Release Liner</b>	Siliconized 1 Side PET

### PRODUCT CHARACTERISTIC

<b>Film Thickness</b>	3 mil (75µ)
<b>*Outdoor Durability</b>	2 Years (ink dependent; see warranty for more details)
<b>Application Temperature</b>	>23°F (-5°C)
<b>Service Temperature Range</b>	-4°F to 248°F (-20°C to 120°C)
<b>Stretching Temperature</b>	140°F - 176°F (60°C - 80°C)
<b>Melting Temperature</b>	498°F (259°C)
<b>Shelf Life</b>	2 years
<b>Storage Conditions</b>	59°F to 72°F (15°C to 22°C); 50 - 55% Relative Humidity*

### PRINTING RECOMMENDATIONS

- Handle material with care prior to printing; use gloves to avoid finger prints.
  - Printing temperature should be 59-86°F (15-30°C) with 30-60% humidity.
  - Set printer to highest print setting for optimal print quality.
- If mounting on glass or backlit substrates, evaluate colour density of the print on a window or in transmitted light.

**DRYTAC®**  
**ADHESIVE SCIENCE**

#### Europe

Filwood Road,  
Fishponds,  
Bristol, BS16 3RY,  
United Kingdom  
[bristol@drytac.com](mailto:bristol@drytac.com)  
Tel: +44 (0) 117 958 6500

#### Canada

30 Driver Road,  
Brampton,  
Ontario, L6T 5V2,  
Canada  
[toronto@drytac.com](mailto:toronto@drytac.com)  
Tel: +1 800.353.2883

#### USA

5401 B Eubank Road,  
Sandston,  
Virginia, 23150,  
USA  
[customerservice@drytac.com](mailto:customerservice@drytac.com)  
Tel: +1 800.280.6013